

Features:

- Standard: IEC60439-3
- Electric ratings: up to 100A, 240/415V, AC 50/60Hz
- No. Of mounted units: 4, 6, 8, 12, 15, 18, 24, 36 ways
- On-load current (A): 100/1-phase, 63/3-phase
- IP Rating: IP40
- Material of body: HIPS, ABS, ABS-UV Fire Resistant
- Transparent Door: AS, UV Resistant PC



Z-MF Series of Flush Mounting

Part No.	Dimensions (mm)				Qty/Ctn (pcs)
	L	W	H	B	
Z-MF4Ways	136	222	93	86	20
Z-MF6Ways	172	222	93	122	20
Z-MF/D6Ways	192	247	93	122	20
Z-MF8Ways	208	222	93	158	20
Z-MF/D8Ways	228	247	93	158	20
Z-MF12Ways	280	222	93	230	10
Z-MF/D12Ways	305	247	93	230	10
Z-MF15Ways	334	222	93	283	10
Z-MF/D15Ways	354	247	93	283	10
Z-MF18Ways	398	252	103	338	5
Z-MF/D18Ways	415	270	103	238	5
Z-MF24Ways	300	345	103	232	5
Z-MF/D24Ways	305	355	103	232	5
Z-MF36Ways	341	503	103	265	5

