



## Features:

- Standard: IEC60439-3
- Electric ratings: up to 63A, 240/415V, AC 50/60Hz
- No. Of mounted units: 1, 2, 4, 6, 8, 12, 18 poles
- IP Rating: IP30
- Material of Body: HIPS, ABS, ABS-UV Fire Resistant
- Lock available



## Z-H series of Surface Mouning

Part No.	Dimensions(mm)			Qty/Ctn(pcs)
	L	W	H	
Z-H 1 Pole	34	130	60	200
Z-H 2 Pole	52	130	60	200
Z-H 4 Pole	87	130	60	100
Z-H 6 Pole	123	160	60	50
Z-H 8 Pole	160	160	60	50
Z-H 12 Pole	260	160	60	20
Z-H 18 Pole	365	160	60	20



## Dimensions(mm)

## Features:

- Standard: IEC60439-3
- Electric ratings: up to 63A, 240/415V, AC 50/60Hz
- No. Of mounted units: 1, 2, 3, 4 poles
- IP Rating: IP30
- Material of Body: HIPS, ABS, ABS-UV Fire Resistant
- Lock available



## Z-HG series of Surface Mouning

Part No.	Dimensions(mm)			Qty/Ctn(pcs)
	L	W	H	
Z-HG 1 Pole	133	35	69	150
Z-HG 2 Pole	133	53	69	100
Z-HG 3 Pole	133	70	69	80
Z-HG 4 Pole	153	88	69	60